



THE SMART SOLUTION FOR ENERGY EFFICIENCY

CONSOLE (CCE) SERIES 0.5 TO 1.5 TON CONSOLE UNITS



ClimateMaster Water-Source Heat Pumps Console (CCE) Series 0.5 to 1.5 Ton Console Units

THE CONSOLE (CCE) SERIES

The CCE series console unit provides a high efficiency WSHP "ductless" solution for spaces where individual, quiet control of the heating and cooling system is important. CCE units are especially ideal where ceiling height and space are limited, or when preserving the integrity of an existing structure. The CCE series meets ASHRAE 90.1 efficiencies, yet maintains small cabinet dimensions.

Available in sizes 1/2 ton (1.76 kW) through 1-1/2 tons (5.3 kW) with numerous cabinet, water piping and control choices, the CCE series offers a wide range of units for most any installation. The CCE has an extended range refrigerant circuit, capable of ground loop (geothermal) applications as well as water loop (boiler-tower) applications. Standard features are many. Microprocessor controls, galvanized steel cabinet, epoxy powder coat paint and TXV refrigerant metering device are just some of the features of the flexible CCE series.

ClimateMaster's exclusive double isolation compressor mounting system makes the CCE series one of the quietest console units on the market. Compressors are mounted on vibration isolation springs to a heavy gauge mounting plate, which is then isolated from the cabinet base with rubber grommets for maximized vibration/sound attenuation. Options such as e-coated air coil, DDC controls, internal pump and factory-installed water solenoid valves allow customized design solutions.

The CCE Series console water-source heat pumps are designed to meet the challenges of today's HVAC demands with a low cost/high value "ductless" solution.

UNIT FEATURES

- Sizes 007 (1/2 ton, 1.76 kW) through 019 (1-1/2 ton, 5.3 kW)
- R410A Refrigerant
- Efficient Rotary compressors
- Meets ASHRAE 90.1 efficiencies
- Two-piece chassis/cabinet design
- Galvanized steel cabinet with durable Polar Ice powder coat finish
- Slope top/aluminum rigid bar supply air grille
- Unique double isolation compressor mounting for quiet operation
- TXV metering device
- Extended range (20 to 120°F, -6.7 to 48.9°C) operation
- ADA approved unit mounted controls, auto or manual-change-over
- Remote-mounted controls available
- Microprocessor controls standard (optional DXM and/or DDC controls)
- LonWorks, BACnet, Modbus and Johnson N2 compatibility options for DDC controls
- Factory-mounted hanger brackets for horizontal units
- Right or left-hand piping arrangement
- Front or bottom return
- Unit Performance Sentinel performance monitoring system (remote controls)
- Eight Safeties Standard
- Wide variety of options including e-coated air coils and internal pumps



New digital controls available in manual and auto changeover

